



Whether being used to highlight architectural elements, to accent specific features of an environment, or for use as task lighting, ELEMENT Merge 1.5 recessed track allows spot heads or pendants to be added directly into the recessed channel at any point along its concealed low-voltage bus system. ELEMENT Merge 1.5 recessed track can make 90° turns in the same plane or perpendicular transitions from ceiling to wall for enhanced architectural interest. All ELEMENT Merge 1.5 recessed track components feature a beveled aperture to integrate seamlessly with architecture for sleek ceiling-to-fixture transitions. Available in 4', 6' and 8' lengths (with a number of connector options) for flangeless installation.

#### **Key Features:**

- Two spot head options: Merge Capsule and Merge Drop-Down
- Twist-and-lock design allows adjustable LED spot heads to be placed anywhere along the bus channel
- Low profile design for use in 2x4 construction
- Optional 90° horizontal turns (same plane) or 90° ceiling-to-wall transitions (not available in Lay-in)
- FreeJack adapter allows the use of any Tech Lighting low-voltage head or pendant

## **SPECIFICATIONS**

VOLTAGE	120V or 277V (Concealed 10 gauge, low-voltage bus bar, order 12-volt remote transformer sold separately)
CEILING APERTURE	1.5" beveled
CEILING APPEARANCE	Flangeless, includes plaster plate, including mitered ends as needed
HOUSING	IC Airtight available in 4', 6' and 8'. IC suitable up to R60 spray foam insulation (Consult Quotes Department for Chicago Plenum option).
TRANSITIONS	Optional 90° horizontal turns (same plane) or 90° ceiling-to-wall
GENERAL LISTING	ETL
CONSTRUCTION	Housing: 20 gauge sheet metal Extrusion: Aluminum
HARDWARE	Steel
FINISH	White Powder Coat
WARRANTY*	1 year

<sup>\*</sup>Visit ELEMENT-lighting.com for specific warranty limitations and details.

Notes: Typical max run length is 40' for the low-voltage bus which can be powered from both sides for a total of 80'; system wattage will impact max run length



MERGE shown flangeless

## **GRIDS**

#### **LINEAR CHANNELS**

SYSTEM NOMINAL LENGTH		CEI	CEILING APPEARANCE		OUTPUT		FINISH	
RLS1	6	4 FT 6 FT 8 FT	RL	RECESSED FLANGELESS	0	NO OUTPUT - 12V BUS ONLY*	W	MATTE WHITE
RLS1				RL		0		W

<sup>\*</sup>TRANSFORMER REQUIRED TO ENERGIZE THE LOW-VOLTAGE BUS.

### **FINISHING KIT**

SYSTEM	TYPE	STYLE	CEILING APPEARANCE	FINISH	
RLS1	FK FINISHING KIT	1 CLOSED ENDCAP	RL RECESSED FLANGELESS	W MATTE WHITE	
RLS1	FK	1	RL	W	

INCLUDES 2 ENDCAPS AND ALL NECESSARY MOUNTING HARDWARE.

TRANSFORMERS\*
(REQUIRED, ORDERED SEPARATELY)

ITEM	DESCRIPTION	DIMMING
700AT060EL 700AT152EL 700AT152ELD010 700AT150T 700AT150T277 700AT302EL 700AT300T	ELECTRONIC, 60W, 120V ELECTRONIC, 150W, 120V ELECTRONIC, 150W, 120V MAGNETIC, 150W, 270V MAGNETIC, 150W, 277V ELECTRONIC, 300W, 120V MAGNETIC, 300W, 120V MAGNETIC, 300W, 277V	ELV 0-10V MAGNETIC MAGNETIC ELV MAGNETIC MAGNETIC MAGNETIC

DO NOT LOAD TRANSFORMER ABOVE 70% OF RATED LOAD DUE TO IN-RUSH CURRENT. \*CONSULT SPEC SHEETS FOR DIMENSIONS.

## PROJECT INFO


FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

Visual Comfort & Co.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

## HOUSING



# **DIMENSIONS**

	LENGTH (A)
4' INDIVIDUAL	48"
6' INDIVIDUAL	72"
8' INDIVIDUAL	96"

Please note that end caps will add 1" to overall length of the fixture