

REFLECTIONS

INDIRECT DOWNLIGHT - REMODEL

Innovative, first-of-its-kind technology in architectural downlights, Reflections combines decorative recessed domes with beautifully controlled, reduced-glare indirect LED illumination. Reflections domes (available in 5", 8" and 12" diameters) are recessed into the ceiling plane and act as reflectors to a completely hidden ring of up-firing LEDs.

The decorative domes: Bloom, Dune, Fleur and Torus consist of beautiful molded geometry for dramatic visual interest with the subtle contrast of light and shadow. The smooth Skye dome creates soft, low-glare general illumination with a peaceful visual aesthetic.

Reflections offers two ceiling appearance options: Flanged for a more traditional ceiling appearance and a field-paintable flange ring, or flangeless for a smooth, mudded-in ceiling appearance.

Pristine design and illumination:

- Reduced glare, indirect illumination (dimnable for enhanced mood-setting options)
- Three aperture options: 5", 8" and 12" (Flanged or Flangeless appearance)
- Beveled, rounded trim edges smoothly and seamlessly integrate into ceiling
- High quality LM80-tested LEDs for consistent long-life performance and color

SPECIFICATIONS

	5"	8"	12"
DELIVERED LUMENS	684	1255	1989
WATTS	9	15	31
EFFICACY	76	84	64
CRI	90+		
CCT OPTIONS	2700K, 3000K, 3500K or Warm Color Dimming (3000K-2000K)		
VOLTAGE	Universal 120V-277V		
LIGHT DISTRIBUTION	Lambertian		
DIMMING¹	0-10V, ELV, TRIAC (down to 5%) EldoLED 0-10V or DALI-2 (down to 0.1%) Lutron Hi-lume EcoSystem (down to 0.1%)		
POWER SUPPLY	Constant current driver with +.9 power factor and +85% efficiency. Serviceable from below the ceiling.		
CEILING APPEARANCE	Flanged or Flangeless		
CEILING THICKNESS	Flanged: 1/2" to 1" Flangeless: No ceiling thickness limitations		
CEILING APERTURE	6" ceiling cutout	8" ceiling cutout	12.5" ceiling cutout
HOUSING	IC Airtight. Suitable up to R60 spray foam insulation.		
FINISH	Flanged trim: White (paintable)		
GENERAL LISTINGS	ETL Listed. Damp Location.		
CALIFORNIA TITLE 24	Registered CEC Appliance Database. Can be used to comply with CEC 2019 Title 24 Part 6 (JA8-2016, JA8-2019).		
L70	50,000 hours min		
WARRANTY²	5 years		

Ordering grids available on page 2.

¹See visualcomfort.com for dimmer compatibility.

²Visit visualcomfort.com for specific warranty limitations and details.

©2023 Visual Comfort & Co. All rights reserved. The Visual Comfort & Co. logo is a registered trademark. Visual Comfort & Co. reserves the right to change specifications for product improvements without notification.



SKYE
SHOWN IN FLANGELESS



DUNE
SHOWN IN FLANGED



TORUS
SHOWN IN FLANGELESS



FLEUR
SHOWN IN FLANGED



BLOOM
SHOWN IN FLANGELESS

REFLECTIONS

INDIRECT DOWNLIGHT - REMODEL

ORDERING GRIDS

HOUSING

PRODUCT	CEILING APPEARANCE	CRI/CCT	DOME PATTERN	HOUSING RATING	DRIVER	FINISH
EDIM5R 5"	RL REMODEL FLANGELESS	927 90 CRI, 2700K	1 SKYE	I IC	120V/277V	W WHITE (PAINTABLE)
EDIM8R 8"	RF REMODEL FLANGED	930 90 CRI, 3000K	2 TORUS		UNIVERSAL PHASE/0-10V 5% (LEAVE BLANK)	
EDIM12R 12"		935 90 CRI, 3500K	3 BLOOM		-ELDO ELDOLED 0.1% 0-10V LINEAR UNV	
		WD 90 CRI, WARM DIM 3000K-2000K	4 FLEUR		-ELDOA ELDOLED 0.1% 0-10V LOGARITHMIC UNV	
			5 DUNE		-ELDD ELDOLED 0.1% DALI-2 UNV	
					-HLECO LUTRON HI-LUME 0.1% ECOSYSTEM	
				I		W




REFLECTIONS


INDIRECT DOWNLIGHT - REMODEL

DOMES / TRIM


5" FLANGED




8" FLANGED




12" FLANGED




5" FLANGELESS




8" FLANGELESS



12" FLANGELESS




REMOTE JUNCTION BOX




J-BOX FOR 5" AND 8"

J-BOX FOR 12"



FLANGED



FLANGELESS WITH INTEGRATED MUD PLATE

REFLECTIONS

INDIRECT DOWNLIGHT - REMODEL

PHOTOMETRICS

Description: Skye 5"
 Total Lumen Output: 684
 Total Power: 9
 Luminaire Efficacy: 76
 Color Temp: 3000K
 CRI: 90+

Description: Skye 8"
 Total Lumen Output: 1255
 Total Power: 15
 Luminaire Efficacy: 84
 Color Temp: 3000K
 CRI: 90+

Description: Skye 12"
 Total Lumen Output: 1989
 Total Power: 31
 Luminaire Efficacy: 64
 Color Temp: 3000K
 CRI: 90+

