

ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

The ENTRA 3" Adjustable Cylinder provides a cost-effective option with a modern aesthetic for residential, hospitality and commercial applications. Engineered with a 0-45° tilt, 360° rotation and interchangeable optics, ENTRA 3" Adjustable Cylinders are a great solution for flexible illumination and aiming light where it's needed. Mounting options include Flush Mount, Surface Mount, Pendant Mount and Conduit Mount. LED is recessed in the cylinder minimizing glare with warm dimming and static white options. Available in Black, Brushed Aluminum, and White (field paintable).

- Tool-free aiming/locking: 0-45° tilt, 360° rotation
- Interchangeable optics: 18°, 25°, 40°, and 60°
- 1-step standard color binning for static white
- Several lens and louver options including Solite Soft Focus



SHOWN IN WHITE

LUMEN MULTIPLIER (CRI/CCT)

CCT	80 CRI MULTIPLIER	90 CRI MULTIPLIER
2700K	—	0.75
3000K	—	0.80
3500K	1.00	—

Lumen output will vary by CCT and CRI. See photometric charts for output information. Data in chart reflects 3500K/80 CRI values, unless otherwise noted.

SPECIFICATIONS

	STATIC WHITE	WARM DIM
WATTAGE	Lumens	Efficacy
12W	1400	116
15W	1800	120
19W	2250	118
27W	2900	107
CRI	80+, 90+	90+
CCT	2700K, 3000K, or 3500K	3000K - 1800K
CBCP	18° - 8,192 25° - 6,907 40° - 4,517 60° - 3,209	
COLOR CONSISTENCY	1-step	2-step
VOLTAGE	120V or 277V	
DIMMING¹	Standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming down to 1% for 12W and 15W, and 5% for 19W and 27W eldoLED 0-10V or DALI-2 down to 0.1% Lutron Hi-lume EcoSystem down to 0.1%	
POWER SUPPLY	Constant current driver with +0.9 power factor and +80% efficiency	
BEAM SPREAD	Interchangeable optics: 18°, 25°, 40°, or 60°	
ADJUSTABILITY	0-45° tilt, 360° rotation	
CEILING APPEARANCE	Flush Mount, Surface Mount (Canopy), Pendant Mount (Canopy), or Conduit Mount (J-Box)	
CONSTRUCTION	Cylinder: Aluminum	
FINISH	Reflector: White, Black, or Brushed Aluminum Cylinder: White, Black, or Brushed Aluminum	
GENERAL LISTINGS	ETL Listed. Damp Location.	
CALIFORNIA TITLE 24	Registered CEC appliance database. Complies with CEC 2019 Title 24 Part 6 (JAB-2016, JAB-2019) (for 90 CRI versions).	
L70	50,000 hours min	
WARRANTY²	5 years	

Data in chart reflects 3500K/80 CRI values, unless otherwise noted.

Ordering grids available on page 2.

¹See visualcomfort.com for dimmer compatibility.

²Visit visualcomfort.com for specific warranty limitations and details.

ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

ORDERING GRIDS

CYLINDER

PRODUCT	MOUNTING	OUTPUT	CRI/CCT	BEAM SPREAD	FUNCTION	DRIVERS	REFLECTOR FINISH ⁷	CYLINDER FINISH
ENCY3R ENTRA CYLINDERS 3" ROUND	F FLUSH MOUNT 1	-L12 12W (1400 LMS)	835 80 CRI, 3500, 1-STEP	1 18°	A ADJUSTABLE	INTEGRATED DRIVERS 120V/277V -UNV UNIVERSAL PHASE/0-10V 1%/5% ⁴	-B BLACK -W WHITE -A BRUSHED ALUMINUM	B BLACK W WHITE A BRUSHED ALUMINUM
	S SURFACE MOUNT (CANOPY)	-L15 15W (1800 LMS)	927 90 CRI, 2700K, 1-STEP	2 25°				
	C CONDUIT MOUNT (J-BOX) ²	-L19 19W (2250 LMS)	930 90 CRI, 3000K, 1-STEP	4 40°				
	P PENDANT MOUNT (CANOPY) ³	-L27 27W (2900 LMS)	9WD 90 CRI, WARM DIM, 3000-1800K, 2-STEP	6 60°				
						REMOTE DRIVERS 120V/277V⁵		
						-ELDO ELDOLED 0.1% 0-10V LINEAR		
						-ELDDA ELDOLED 0.1% 0-10V LOGARITHMIC		
						-ELDD ELDOLED 0.1% DALI-2		
						-HLECO LUTRON HI-LUME 0.1% ECOSYSTEM		
ENCY3R						-	A	-

For dimming details, refer to dimmer compatibility chart.

Standard cylinder reflectors do not accommodate any lens accessories. To use with lens accessories (max. 2), order the ENCY3LK Lens/Louver Kit.

¹F - Flush Mount includes adapter plate to assemble to standard 4" square or octagonal junction box prior to ceiling install.

²C - Conduit Mount includes custom junction box assembled at/below the ceiling.

³P - Pendant Mount for use with ECPS Cylinders pendant stems.

⁴UNV - Universal dimming is reverse-phase, forward-phase, TRIAC, and 0-10V, 277V is only compatible with 0-10V dimming. Dims down to 1% for 12W and 15W outputs, and 5% for 19W and 27W outputs.

⁵Remote drivers ship in 4" x 8" x 1.8" black enclosure for remote location mounting.

REPLACEMENT OPTICS

PRODUCT	BEAM SPREAD
353E4LEDCOPT	18 18° 25 25° 40 40° 60 60°
353E4LEDCOPT	-

REFLECTOR OPTIC TOOL

PRODUCT ¹
ENCY3TR ENTRA CYLINDERS 3" REFLECTOR TOOL
ENCY3TR

¹It is highly recommended to order a reflector optic tool when purchasing lens/louver kits as this will make removal of the existing reflector significantly easier.

LENS/LOUVER KIT

PRODUCT ¹	TYPE	REFLECTOR FINISH
ENCY3LK	SB SANDBLASTED LENS	-B BLACK
	SF SOLITE SOFT FOCUS LENS	-W WHITE
	LL LINEAR SPREAD LENS	-A BRUSHED ALUMINUM
	EC EGGRATE LOUVER	
ENCY3LK	-	

¹Required for use with lenses or louvers for Cylinders. Lens/louver kits include a reflector and 1 lens. To add additional lenses (max. 2), see accessories page. It is highly recommended to order a reflector optic tool when purchasing lens/louver kits as this will make removal of the existing reflector significantly easier.

PENDANT STEMS

PRODUCT ¹	LENGTH ²	FINISH
ECPS	12 12"	B BLACK
	24 24"	W WHITE
	36 36"	A BRUSHED ALUMINUM
	48 48"	
	60 60"	
	72 72"	
ECPS	-	

¹Required for Pendant Mount only.
²Consult Quotes Department for custom lengths to the inch.

VAULTED CEILING ADAPTER

PRODUCT	FINISH
ECVA PENDANT MOUNT ¹	B BLACK
ECVAD SURFACE MOUNT ²	W WHITE
	A BRUSHED ALUMINUM

¹For use with Pendant Mount. Adds 1.7" to the overall length of the stem. Accommodates slopes up to 45 degrees.
²For use with Surface Mount. Accommodates slopes up to 45 degrees.

ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

CYLINDERS



FLUSH MOUNT



WHITE

BRUSHED ALUMINUM

BLACK




CONDUIT MOUNT (J-BOX)



WHITE

BRUSHED ALUMINUM

BLACK






SURFACE MOUNT (CANOPY)



WHITE

BRUSHED ALUMINUM

BLACK





PENDANT MOUNT (CANOPY)




WHITE

BRUSHED ALUMINUM

BLACK



REMOTE DRIVER J-BOX



ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

PHOTOMETRICS

Description: 3" Cylinder Adjustable
18° Beam - 0° Tilt,
90 CRI, 3000K

Input Power (Watts): 32.9
Input Power Factor: 0.99
Absolute Luminous
Flux (Lumens): 2494
Lumen Efficacy
(Lumens per Watt): 76

Output difference between CCTs - 5%, CRIs - 15%.

Description: 3" Cylinder Adjustable
25° Beam - 0° Tilt,
90 CRI, 3000K

Input Power (Watts): 32.7
Input Power Factor: 0.98
Absolute Luminous
Flux (Lumens): 2456
Lumen Efficacy
(Lumens per Watt): 75







Description: 3" Cylinder Adjustable
40° Beam - 0° Tilt,
90 CRI, 3000K

Input Power (Watts): 32.8
Input Power Factor: 0.98
Absolute Luminous
Flux (Lumens): 2584
Lumen Efficacy
(Lumens per Watt): 79

ANGLE	0°	45°	90°
0°	8192	8192	8192
5°	7438	7514	7532
10°	5277	5300	5297
15°	3190	3214	3209
20°	1898	1908	1900
25°	1066	1077	1064
30°	610	626	608
35°	319	386	325
40°	161	249	162
45°	94	145	94
50°	62	77	63
55°	37	49	37
60°	25	30	25
65°	12	16	13
70°	1	7	2
75°	0	0	0
80°	0	0	0
85°	0	0	0
90°	0	0	0

ANGLE	0°	45°	90°
0°	6907	6907	6907
5°	6578	6568	6565
10°	5455	5476	5467
15°	3575	3584	3595
20°	1856	1910	1947
25°	997	1040	1057
30°	623	654	660
35°	330	433	358
40°	153	276	165
45°	88	149	96
50°	57	73	61
55°	32	44	35
60°	19	25	21
65°	8	12	9
70°	0	4	1
75°	0	0	0
80°	0	0	0
85°	0	0	0
90°	0	0	0

ANGLE	0°	45°	90°
0°	4517	4517	4517
5°	4385	4393	4402
10°	4053	4071	4076
15°	3498	3518	3534
20°	2595	2648	2698
25°	1635	1620	1598
30°	860	850	804
35°	374	429	396
40°	179	224	190
45°	101	123	107
50°	60	75	64
55°	31	47	32
60°	19	26	20
65°	7	12	8
70°	1	3	1
75°	0	0	0
80°	0	0	0
85°	0	0	0
90°	0	0	0



ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

PHOTOMETRICS

Description: 3" Cylinder Adjustable
 60° Beam - 0° Tilt,
 80 CRI, 3000K

Input Power (Watts): 30.7



Input Power Factor: 0.98

Absolute Luminous
 Flux (Lumens): 3178

Lumen Efficacy
 (Lumens per Watt): 103.4

Output difference between CCTs - 5%, CRIs - 15%.

ANGLE	0°	45°	90°
0°	3209	3209	3209
5°	3215	3152	3158
10°	3103	3067	3068
15°	2869	2852	2881
20°	2428	2393	2468
25°	1881	1814	1930
30°	1398	1324	1441
35°	982	939	1038
40°	597	603	681
45°	334	359	393
50°	186	202	210
55°	89	118	98
60°	46	74	50
65°	25	38	27
70°	6	15	7
75°	4	4	4
80°	3	3	3
85°	1	1	1
90°	0	0	0



ENTRA™ 3" CYLINDER

ADJUSTABLE CYLINDER

PROJECT INFORMATION

JOB NAME AND INFORMATION

FIXTURE TYPE AND QUANTITY

NOTES
