



Halogen MR16 remodel downlight with architectural appearance. 0°- 30° tilt and 361° internal rotation, includes hot aiming and locking.


- 0°-30° tilt and 361° rotation, in only a 5.75" deep housing
- Compatible with LED MR16 replacement lamp. LED MR16 requires no load electronic transformer (12 watt max).
- · Power supplies can be accessed through the aperture
- · Accepts 2 optical controls and an optional trim mounted lens
- · Glare reducing snoot integrated
- Lensed and shower options include Solite[™] soft focus lens at aperture
- Accepts standard E3 New Construction flanged trims

Installation

- Use standard 3-7/8" hole saw or 3-7/8" cut-out (template included) for flanged trims.
- Set screws engage with expanding collar for robust mounting within the ceiling cut-out

SPECIFICATIONS

LAMP	Low-voltage Halogen MR16 lamp. Compatible with LED MR16 replacement lamps.
WATTS	Halogen: 75 Non-IC only
VOLTAGE	120V or 277V
DIMMING*	ELV or MLV (Dimming dependent on transformer type).
ADJUSTABILITY	Hot aiming, including 0°-30° Tilt and 361° rotation
CEILING APPEARANCE	Flanged (accommodates up to 1" drywall or wood ceiling thickness)
CEILING APERTURE	3-7/8"
HOUSING	Non-IC
POWER SUPPLY	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16 compatibility
GENERAL LISTING	ETL listed. Damp listed. Shower version wet listed.
CONSTRUCTION	Housing: Heavy gauge cold rolled steel Trims: Die-cast aluminum
FINISH	Housing: Black Trims: Antique Bronze, Black, Satin Nickel, White (paintable)
WARRANTY**	1 year



shown in flanged bevel square


^{*}See ELEMENT-lighting.com for dimmer compatibility.
**Visit ELEMENT-lighting.com for specific warranty limitations and details.

TRIMS

ROUND




FLANGED BEVEL



FLANGED FLAT

SQUARE



FLANGED BEVEL



FLANGED FLAT

FINISH



ANTIQUE BRONZE



BLACK



SATIN NICKEL



WHITE (PAINTABLE)

3" HOUSING





GRIDS

HOUSING

PRODUCT SERIES	CEILING APPEARANCE	LAMP	FUNCTION	HOUSING RATING	TRANSFORMER	WATTAGE RESTRICTION (PER SOCKET)	VOLTAGE
E3R ELEMENT 3" ROUND E3S ELEMENT 3" SQUARE	RF FLANGED REMODEL	-H HALOGEN MR16	A ADJUSTABLE	N NON-IC	E ELECTRONICM MAGNETICN NO LOAD ELECTRONIC	NONE (LEAVE BLANK) -WR WATTAGE RESTRICTION*	120 VOLT (LEAVE BLANK) 277 277 VOLT
	RF	-H	Δ	N			

TRIM

PRO	DUCT SERIES	CE	ILING APPEARANCE	ST	YLE	AP	ERTURE	FIN	IISH
E3R E3S	ELEMENT 3" ROUND ELEMENT 3" SQUARE	F	FLANGED	_	BEVEL FLAT		NO LENS SHOWER LENSED	Z B S W	ANTIQUE BRONZE BLACK SATIN NICKEL WHITE
			F			-			

PROJ	ЕC		NΗ	\cup
------	----	--	----	--------

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES



TRIMS ARE REQUIRED AND MUST BE ORDERED SEPARATELY.
*TO INCLUDE WATTAGE RESTRICTION LABEL, SPECIFY -WR AT THE END OF THE HOUSING ITEM NUMBER AND SPECIFY WATTAGE (EXAMPLE: -WR37).