




This specification grade LED wall wash fixture combines high output and performance with an architectural ceiling appearance. Each of the five optional LED modules come factory positioned for optimal light performance and distribution.

- Five LED module options to meet all performance requirements
- Trim is angled with frosted linear spread lens and light shaping film to create consistent horizontal and vertical illumination
- Lensed and shower aperture includes Solite™ soft focus lens

## SPECIFICATIONS


							
	CITIZEN			CITIZEN WARM DIM		XICATO	
	MAX OUTPUT	HIGH OUTPUT	LOW OUTPUT	HIGH OUTPUT	LOW OUTPUT	STANDARD SERIES	ARTIST SERIES
DELIVERED LUMENS	2600 / 2085	2494 / 2041	1651 / 1319	1875	1042	1734	1522
WATTS	32	32	18	32	18	24	25
EFFICACY	81 / 65	78 / 63	91 / 73	58	58	72	61
CRI	80+ / 90+	80+ / 90+	80+ / 90+	90+		80+	95+
CCT OPTIONS	2700K, 3000K or 3500K			3000K-1800K Warm Dim		2700K, 3000K or 3500K***	
VOLTAGE	120V or 277V						
DIMMING*	TRIAC, ELV, 0-10V (Down to 5%) Lutron Hi-Lume Ecosystem Fade-To-Black or PWM (Down to 1%) eldoLED 0-10V or Dali (Down to 0%)						
POWER SUPPLY	Constant current: driver with +.9 power factor and +80% efficiency						
OPTICS	Ships with optimized angle for wall wash applications						
ADJUSTABILITY	361° rotation, 45° collar rotation						
CEILING APPEARANCE	Flanged (Accommodates up to 1" ceiling thickness) or Flangeless						
CEILING APERTURE	4-1/2" ceiling cut-out						
HOUSING	IC Airtight, Non-IC Airtight, Chicago Plenum. IC suitable for insulation rating up to R60						
CONSTRUCTION	Housing: Heavy gauge cold rolled steel Trims: Die cast aluminum						
FINISH	Housing: Black Powder Coat Trims: Antique Bronze, Black, Satin Nickel, White (paintable)						
GENERAL LISTING	ETL listed. Damp listed. Shower version wet listed.						
CALIFORNIA TITLE 24	Registered CEC Appliance Database. Can be used to comply with CEC 2016 Title 24 Part 6 for 90 CRI versions.						
LED LIFETIME	L70; 50,000 hours						
WARRANTY**	5 years						

\*See ELEMENT-lighting.com for dimmer compatibility.

\*\*Visit ELEMENT-lighting.com for specific warranty limitations and details.

\*\*\*3500K Xicato module not available for Artist series.

Data in chart reflects 3000K/80 CRI values unless noted. Consult Quotes Dept for alternate or custom driver selections. Accepts two optical controls and an optional trim-mounted lens.




shown in flangeless wall wash square

### Installation


- Includes adjustable hangar bars. Includes butterfly brackets that attach to the side of the housing and are vertically adjustable with a wing nut
- Incorporates integral gunsights for positioning with laser level or string
- 45° adjustable collar rotation after installation assures square trims are perfectly aligned

TRIMS

ROUND




FLANGELESS WALL WASH




FLANGED WALL WASH

SQUARE



FLANGELESS WALL WASH



FLANGED WALL WASH

FINISH



ANTIQUE  
BRONZE



BLACK




SATIN  
NICKEL




WHITE  
(PAINTABLE)

4" HOUSING

MAX CEILING THICKNESS: 1"



NON-IC / CHICAGO PLENUM



IC AIRTIGHT

## GRIDS

### HOUSING

PRODUCT SERIES	CEILING APPEARANCE	FUNCTION	LAMP	HOUSING RATING	DRIVER	VOLTAGE
<b>E4R</b> ELEMENT 4" ROUND	<b>L</b> FLANGELESS	<b>W</b> WALL WASH	<b>-LV827</b> CITIZEN 80 CRI, 2700K, MAX OUTPUT*	<b>I</b> IC AIRTIGHT	STANDARD ELV (LEAVE BLANK)	120 VOLT (LEAVE BLANK)
<b>E4S</b> ELEMENT 4" SQUARE	<b>F</b> FLANGED		<b>-LV830</b> CITIZEN 80 CRI, 3000K, MAX OUTPUT*	<b>N</b> NON-IC AIRTIGHT	0-10V DIMMING	<b>-277</b> 277 VOLT
			<b>-LV835</b> CITIZEN 80 CRI, 3500K, MAX OUTPUT*	<b>C</b> CHICAGO PLENUM	ELDOLED 0% 0-10V LINEAR	
			<b>-LV927</b> CITIZEN 90 CRI, 2700K, MAX OUTPUT*		ELDOLED 0% 0-10V LOGARITHMIC	
			<b>-LV930</b> CITIZEN 90 CRI, 3000K, MAX OUTPUT*		ELDOLED 1% 0-10V LINEAR	
			<b>-LV935</b> CITIZEN 90 CRI, 3500K, MAX OUTPUT*		ELDOLED 0% 0-10V LOGARITHMIC	
			<b>-LH827</b> CITIZEN 80 CRI, 2700K, HIGH OUTPUT*		ELDOLED 0% DALI	
			<b>-LH830</b> CITIZEN 80 CRI, 3000K, HIGH OUTPUT*		HI-LUME 1% 2 WIRE / PWM†	
			<b>-LH835</b> CITIZEN 80 CRI, 3500K, HIGH OUTPUT*		HI-LUME 1% ECO-SYSTEM	
			<b>-LH927</b> CITIZEN 90 CRI, 2700K, HIGH OUTPUT*		FADE-TO-BLACK	
			<b>-LH930</b> CITIZEN 90 CRI, 3000K, HIGH OUTPUT*			
			<b>-LH935</b> CITIZEN 90 CRI, 3500K, HIGH OUTPUT*			
			<b>-LHWD</b> CITIZEN 90 CRI WARM DIM 3000-1800K, HIGH OUTPUT*			
			<b>-LO827</b> CITIZEN 80 CRI, 2700K, LOW OUTPUT			
			<b>-LO830</b> CITIZEN 80 CRI, 3000K, LOW OUTPUT			
			<b>-LO835</b> CITIZEN 80 CRI, 3500K, LOW OUTPUT			
			<b>-LO927</b> CITIZEN 90 CRI, 2700K, LOW OUTPUT			
			<b>-LO930</b> CITIZEN 90 CRI, 3000K, LOW OUTPUT			
			<b>-LO935</b> CITIZEN 90 CRI, 3500K, LOW OUTPUT			
			<b>-LOWD</b> CITIZEN 90 CRI WARM DIM 3000-1800K, LOW OUTPUT			
			<b>-XI27</b> XICATO, 80+ CRI, 2700K			
			<b>-XI30</b> XICATO, 80+ CRI, 3000K			
			<b>-XI35</b> XICATO, 80+ CRI, 3500K			
			<b>-XA27</b> XICATO ARTIST, 95+ CRI, 2700K			
			<b>-XA30</b> XICATO ARTIST, 95+ CRI, 3000K			

W

TRIMS ARE REQUIRED AND MUST BE ORDERED SEPARATELY. \*MAX & HIGH OUTPUT HI-LUME 2-WIRE NOT AVAILABLE IN IC AIRTIGHT HOUSING. †HL2W - TWO WIRE LOW-VOLTAGE ELECTRONIC DIMMING, 120 VOLT ONLY.

### TRIM

PRODUCT SERIES	CEILING APPEARANCE	FUNCTION	FINISH
<b>E4R</b> ELEMENT 4" ROUND	<b>L</b> FLANGELESS	<b>W</b> WALL WASH	<b>-Z</b> ANTIQUE BRONZE
<b>E4S</b> ELEMENT 4" SQUARE	<b>F</b> FLANGED UP TO 1" CEILING THICKNESS		<b>-B</b> BLACK
			<b>-S</b> SATIN NICKEL
			<b>-W</b> WHITE

W

## PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES

**ELEMENT**  
by Tech Lighting®

GENERATION BRANDS  
7400 Linder Avenue, Skokie, Illinois 60077  
T 847.410.4400 F 847.410.4500



© 2017 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.

# 4" LED WALL WASH

## PHOTOMETRICS: WALL WASH

DESCRIPTION: 4" LED Wall Wash  
90 CRI, 3000K

MODEL: E4 Citizen LED



INPUT POWER (WATTS): 32.7

INPUT POWER FACTOR: 0.98

ABSOLUTE LUMINOUS FLUX (LUMENS): 2039\*

LUMEN EFFICACY (LUMENS PER WATT): 62.3

ANGLE	0°	45°	90°
0°	8192	8192	8192
5°	7438	7514	7532
10°	5277	5300	5297
15°	3190	3214	3209
20°	1898	1908	1900
25°	1066	1077	1064
30°	610	626	608
35°	319	386	325
40°	161	249	162
45°	94	145	94
50°	62	77	63
55°	37	49	37
60°	25	30	25
65°	12	16	13
70°	1	7	2
75°	0	0	0
80°	0	0	0
85°	0	0	0
90°	0	0	0



\*For 90 CRI values, multiply by 0.8.

GENERATION BRANDS



2017 Tech Lighting, L.L.C. All rights reserved. The "Element" graphic is a registered trademark of Element. Element reserves the right to change specifications for product improvements without notification.

**ELEMENT**  
by Tech Lighting®

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500